

# **Dipping Light Jordi Canudas**



# Dipping light Jordi Canudas

Beyond its function as a lamp, the Dipping Light seeks to excite. When it's turned on, its different shades of paint sift the light, creating a magical ambient effect. When it's off, its colored glass sphere is an object charged with beauty, and an

eye-catching design piece for a shelf, bedside, or table. The various layers of paint draw concentric circles and capture the light, moderating its intensity. The paint becomes the shade, colouring and texturizing the light.







## Dipping Light

## Code

A691-468-3515-27K A691-468-4515-27K A691-468-3015-27K A691-468-4015-27K A691-468-4715-27K A691-468-3715-27K Finish White - Brushed Brass Green - Brushed Brass Amber - Brushed Brass Burgundy - Brushed Brass Chocolate - Brushed Brass Cream - Brushed Brass

Dimmable: No

Materials Body: Metal Diffuser: Brilliant white blown glass globe with layered paint

Product details Cable length: 6.6 ft Wire installation: Plug-in Cord color: Black Switch location: In-line

Dry locations only



Electrical Electrical Rating: 120-240VAC 50-60Hz 4W Light source: 123Im CCT: 2700K CRI: 80



8.74"



### **Dipping Light S**



Cable length: 5.75 ft Wire installation: Plug-in Cord color: Black Switch location: In-line

Dry locations only



### **Dipping Light M**

Code A691-470-3515-27K A691-470-4515-27K A691-470-3015-27K A691-470-4015-27K A691-470-4715-27K A691-470-3715-27K Finish White - Brushed Brass Green - Brushed Brass Amber - Brushed Brass Burgundy - Brushed Brass Chocolate - Brushed Brass Cream - Brushed Brass

Dimmable Yes Integrated dimmer: Yes Dimming protocols: Progressive dimmer from 0 to 100

Product details Cable length: 5.75 ft Wire installation: Plug-in Cord color: Black Switch location: In-line

Materials Body: Metal Diffuser: Brilliant white blown glass globe with layered paint

Dry locations only



▲ WARNING. California Proposition 65 Warning for California Consumers. This product can expose you to chemicals including wood dust and lead which are known to the State of California to cause cancer or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Watch the video	marsetusa@marset.com www.marset.com	Collection	
Download	Photometric data file (LDT or IES) 2D, 3D, Photmetric Data Assembly instructions		•

Electrical Rating: 85-264VAC 50-60Hz 11W Luminaire: 312lm CCT: 2700K CRI: 90





